

Safety Data Sheet



SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Techron HD

Product Number(s): 003101, 803101

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Fuel Additive

1.3 Details of the supplier of the safety data sheet

Chevron Belgium NV
Technologiepark-Zwijnaarde 2
B-9052 Gent
Belgium
email : eumsds@chevron.com

1.4 Emergency telephone number

Transportation Emergency Response

Europe: 0044/(0)18 65 407333

Health Emergency

Europe: 0044/(0)18 65 407333

Poison Control Center: Belgium: 0032/(0)70 245 245

Product Information

Product Information: FAX number: 0032/(0)9 293 72 22

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLP CLASSIFICATION: Eye irritation: Category 2, H319. Skin irritation: Category 2, H315. Target organ toxicant (central nervous system): Category 3, H336.

2.2 Label elements

Under the criteria of Regulation (EC) No 1272/2008 (CLP):



Signal Word: Warning

Health Hazards: Causes serious eye irritation (H319). Causes skin irritation (H315). May cause drowsiness or dizziness (H336).

- contains: Naphtha (petroleum), hydrotreated heavy
Branched alkanol

PRECAUTIONARY STATEMENTS:

Prevention: Use only outdoors or in a well-ventilated area (P271).

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing (P305+P351+P338). IF ON SKIN: Wash with plenty of soap and water (P302+P352). Call a POISON CENTER or doctor/physician if you feel unwell (P312).

Storage: Store locked up (P405).

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international regulations (P501).

2.3 Other hazards

This product is not, or does not contain, a substance that is a potential PBT or a vPvB. Repeated exposure may cause skin dryness or cracking (EUH066).

SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

3.2 Mixtures

This material is a mixture.

COMPONENTS	CAS NUMBER	EC NUMBER	REGISTRATION NUMBER	CLP CLASSIFICATION	AMOUNT
Naphtha (petroleum), hydrotreated heavy	64742-48-9	265-150-3	**	Asp. Tox. 1/H304; Flam. Liq. 3/H226; STOT SE 3/H336	30 - 60 %weight
Branched alkanol	Trade secret	Confidential	01-2119487289-2 0	Aquatic Chronic 3/H412; Eye Irrit. 2/H319; Acute Tox. 4/H302; Skin Irrit. 2/H315; STOT SE 3/H336	10 - 30 %weight
Highly refined mineral oil (C15 - C50)	Mixture	*	***	None	10 - 30 %weight
Butanedioic acid, polyisobutenyl derivs.	68610-89-9	614-666-0	**	None	10 - 20 %weight

The full text of all CLP H-statements is shown in Section 16.

*Contains one or more of the following EINECS numbers: 265-090-8, 265-091-3, 265-096-0, 265-097-6, 265-098-1, 265-101-6, 265-155-0, 265-156-6, 265-157-1, 265-158-7, 265-159-2, 265-160-8, 265-161-3, 265-166-0, 265-169-7, 265-176-5, 276-735-8, 276-736-3, 276-737-9, 276-738-4, 278-012-2.

**Not available or substance is not currently required for registration under REACH.

*** Contains one or more of the following REACH registration numbers: 01-2119488706-23, 01-2119487067-30, 01-2119487081-40, 01-2119483621-38, 01-2119480374-36, 01-2119488707-21, 01-2119467170-45, 01-2119480375-34, 01-2119484627-25, 01-2119480132-48, 01-2119487077-29, 01-2119489287-22, 01-2119480472-38, 01-2119471299-27, 01-2119485040-48, 01-2119555262-43, 01-2119495601-36, 01-2119474889-13, 01-2119474878-16.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures

Eye: Flush eyes with water immediately while holding the eyelids open. Remove contact lenses, if worn, after initial flushing, and continue flushing for at least 15 minutes. Get immediate medical attention.

Skin: Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: If swallowed, get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Inhalation: Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue or if any other symptoms develop.

4.2 Most important symptoms and effects, both acute and delayed

IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

Eye: Contact with the eyes causes severe irritation. Symptoms may include pain, tearing, reddening, swelling and impaired vision.

Skin: Contact with the skin causes irritation. Skin contact may cause drying or defatting of the skin. Symptoms may include pain, itching, discoloration, swelling, and blistering.

Ingestion: May be irritating to mouth, throat, and stomach. Symptoms may include pain, nausea, vomiting, and diarrhea.

Inhalation: Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing. Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS: Excessive or prolonged exposure to this material may cause central nervous system effects. Symptoms may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. Extreme exposures may cause respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable.

SECTION 5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

5.2 Special hazards arising from the substance or mixture

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

5.3 Advice for firefighters

This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition in vicinity of spilled material. Refer to Sections 5 and 8 for more information.

6.2 Environmental precautions

Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater.

6.3 Methods and material for containment and cleaning up

Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil and dispose of in a manner consistent with applicable requirements. Place other contaminated materials in disposable containers and dispose of in a manner consistent with applicable requirements. Report spills to local authorities as appropriate or required.

6.4 Reference to other sections

See sections 8 and 13.

SECTION 7 HANDLING AND STORAGE

7.1 Precautions for safe handling

General Handling Information: The maximum handling temperature is 51°C. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not breathe vapor or fumes. Wash thoroughly after handling. Keep out of the reach of children.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly

returned to a drum reconditioner or disposed of properly.

7.2 Conditions for safe storage, including any incompatibilities

General Storage Information: The maximum storage temperature is 45°C. DO NOT USE OR STORE near heat, sparks, flames, or hot surfaces . USE AND STORE ONLY IN WELL VENTILATED AREA. Keep container closed when not in use.

7.3 Specific end use(s): Fuel Additive

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

8.1 Control parameters

Occupational Exposure Limits:

Component	Country/ Agency	TWA	STEL	Ceiling	Notation
Highly refined mineral oil (C15 - C50)	Belgium	5 mg/m3	10 mg/m3	--	--

Consult local authorities for appropriate values.

8.2 Exposure controls

ENGINEERING CONTROLS:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

Skin Protection: Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Suggested materials for protective gloves include: Nitrile (0.4mm @ >480') EN374, Nitrile (0.1mm @ 240-480') EN374, Viton Butyl (0.7mm @ >480') EN374.

Respiratory Protection: Determine if airborne concentrations are below the recommended occupational exposure limits for jurisdiction of use. If airborne concentrations are above the acceptable limits, wear an approved respirator that provides adequate protection from this material, such as: If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

ENVIRONMENTAL EXPOSURE CONTROLS:

See relevant Community environmental protection legislation or the Annex, as applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

9.1 Information on basic physical and chemical properties

Appearance

Color: Amber

Physical State: Liquid

Odor: Characteristic

Odor Threshold: No data available

pH: Not Applicable

Freezing Point: Not Applicable

Initial Boiling Point: >315°C (599°F)

Flashpoint: (Pensky-Martens Closed Cup) 69 °C (156 °F) (Typical)

Evaporation Rate: No data available

Flammability (solid, gas): No Data Available

Flammability (Explosive) Limits (% by volume in air):

Lower: Not Applicable Upper: Not Applicable

Vapor Pressure: <0.01 mmHg @ 37.8 °C (100 °F)

Vapor Density (Air = 1): >1

Density: 0.874 kg/l @ 15°C (59°F)

Solubility: Soluble in hydrocarbons; insoluble in water

Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: No data available

Decomposition temperature: No data available

Viscosity: 80 mm²/s @ 40°C (104°F) (Typical)

Explosive Properties: No Data Available

Oxidising properties: No Data Available

9.2 Other Information: No Data Available

SECTION 10 STABILITY AND REACTIVITY

10.1 Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.2 Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions: Hazardous polymerization will not occur.

10.4 Conditions to Avoid: Not applicable

10.5 Incompatible materials to avoid: Not applicable

10.6 Hazardous decomposition products: None known (None expected)

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Serious Eye Damage/Irritation: The eye irritation hazard is based on evaluation of data for similar materials or product components.

Skin Corrosion/Irritation: The skin irritation hazard is based on evaluation of data for similar materials or product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for similar materials or product components.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for similar materials or product components.

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for similar materials or product components.

Acute Toxicity Estimate (oral): Not Applicable

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for similar materials or product components.

Germ Cell Mutagenicity: The hazard evaluation is based on data for components or a similar material.

Carcinogenicity: The hazard evaluation is based on data for components or a similar material.

Reproductive Toxicity: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Single Exposure: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Repeated Exposure: The hazard evaluation is based on data for components or a similar material.

Aspiration Toxicity: No data available

ADDITIONAL TOXICOLOGY INFORMATION:

In accordance with the Directive 94/69/EC (21st ATP to DSD), Nota L, reference IP 346/92: "DMSO Extraction Method", we have determined that the base oils used in this preparation are not carcinogenic.

SECTION 12 ECOLOGICAL INFORMATION

12.1 Toxicity

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

12.2 Persistence and degradability

The product has not been tested. The statement has been derived from the properties of the individual components.

12.3 Bioaccumulative potential

Bioconcentration Factor: No Data Available

Octanol/Water Partition Coefficient: No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a potential PBT or a vPvB.

12.6 Other adverse effects

No other adverse effects identified.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

In accordance with European Waste Catalogue (E.W.C.) the codification is the following: 07 07 99

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

ADR/RID

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

- 14.1 UN number: Not applicable
- 14.2 UN proper shipping name: Not applicable
- 14.3 Transport hazard class(es): Not applicable
- 14.4 Packing group: Not applicable
- 14.5 Environmental hazards: Not applicable
- 14.6 Special precautions for user: Not applicable

ICAO

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

- 14.1 UN number: Not applicable
- 14.2 UN proper shipping name: Not applicable
- 14.3 Transport hazard class(es): Not applicable
- 14.4 Packing group: Not applicable
- 14.5 Environmental hazards: Not applicable
- 14.6 Special precautions for user: Not applicable

IMO

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

- 14.1 UN number: Not applicable
- 14.2 UN proper shipping name: Not applicable
- 14.3 Transport hazard class(es): Not applicable
- 14.4 Packing group: Not applicable
- 14.5 Environmental hazards: Not applicable
- 14.6 Special precautions for user: Not applicable
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATORY LISTS SEARCHED:

01=EU. Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances.
02=EU Directive 90/394/EEC: Carcinogens at work.
03=EU Directive 92/85/EEC: Pregnant or breastfeeding workers.
04=EU Directive 96/82/EC (Seveso II): Article 9.
05=EU Directive 96/82/EC (Seveso II): Articles 6 and 7.
06=EU Directive 98/24/EC: Chemical agents at work.
07=EU Directive 2004/37/EC: On the protection of workers.
08=EU Regulation EC No. 689/2008: Annex 1, Part 1.
09=EU Regulation EC No. 689/2008: Annex 1, Part 2.
10=EU Regulation EC No. 689/2008: Annex 1, Part 3.
11=EU Regulation EC No. 850/2004: Prohibiting and restricting persistent organic pollutants (POPs).
12=EU REACH, Annex XVII: Restrictions on manufacture, placing on the market and use of certain dangerous substances, mixture & article.
13=EU REACH, Annex XIV: Candidate List of Substances of Very High Concern for Authorization (SVHC).

The following components of this material are found on the regulatory lists indicated.

Naphtha (petroleum), hydrotreated heavy 01, 02, 03, 06

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: DSL (Canada), KECI (Korea), PICCS (Philippines), TSCA (United States).

One or more components does not comply with the following chemical inventory requirements: AICS (Australia), ENCS (Japan), IECSC (China).

15.2 Chemical safety assessment

No chemical safety assessment.

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: This revision updates the following sections of this Material Safety Data Sheet: 1-16

Revision Date: APRIL 30, 2015

Full text of CLP H-statements:

H304; May be fatal if swallowed and enters airways
H412; Harmful to aquatic life with long lasting effects
H319; Causes serious eye irritation
H226; Flammable liquid and vapor
H302; Harmful if swallowed
H315; Causes skin irritation
H336; May cause drowsiness or dizziness

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
CVX - Chevron	CAS - Chemical Abstract Service Number

NQ - Not Quantifiable

Prepared according to the criteria of EU Regulation 1907/2006 by the Chevron Energy Technology Company, 100 Chevron Way, Richmond, California 94802.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

No Annex
